



Learning Objectives for this Session

- Compare the present and predicted future affordability of net-zero energy homes.
- Provide an estimate of required PV price for NZEH to be an optimal solution in 2030.
- Describe measures leading to market-rate net-zero houses.
- Describe the temperature distribution due to minimally distributed heating.
 Explain that whether or not an overall net-zero balance is achieved is highly dependent on the user.

• Describe that in very efficient homes, standby loads become more and more important and unnecessary standby losses (for example a crankcase heater for a heat pump) can sum up to a significant part of the overall energy consumption

ASHRAE is a Registered Provider with The American Institute of Architects Continuing Education Systems. Credit earned on completion of this program will be exported to ASHRAE Records for AIA members. Certificates of Completion for non-AIA members are available on request.

This program is registered with the AIA/ASHRAE for continuing professional education. As such, it does not include content that may be deemed or construed to be an approval or endorsement by the AIA of any material of construction or any method or manner of handling, using, distributing, or dealing in any material or product. Questions related to specific materials, methods, and services will be addressed at the conclusion of this presentation.



12" double stud walls 2x4s, 16" OC outer, 24" OC inner 0.5 lb/cf spray foam, R-4/in about R-45 total



12" double stud walls 2x4s, 16" OC outer, 24" OC inner 0.5 lb/cf spray foam, R-4/in

























